

## Tubo 50

20W / 2675lm / 3000K / DALI / Diffuse /  
1472mm

62586



Design: Eduardo Souto de Moura

Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 50mm diameter.

Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that

prevents condensation within luminaire.


Fitting accessories ordered separately.


LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP67 | IK08 | 230Vac | 50/60Hz



 LED	3000K	Light Source	Luminaire
Power	20W	24,4W	
Flux	3575lm	2675lm	
Efficiency	179lm/W	110lm/W	
LOR	-	75%	
UGR	-	<25	




Beam angle  
Diffuse

## Application



**Weight**  
**1,6Kg**



## Finishes

☐ .25 Frost

Mandatory

**43701 Surface fitting accessory**

**43705 Pendant fitting accessory**

Optional

**59057** Stainless steel fitting accessory

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 28004772