

Tubo 70

54W / 7040lm / 3000K / DALI / Diffuse /
2312mm

62685



Design: Eduardo Souto de Moura
Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 70mm diameter.
Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire.
Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP67 | IK08 | 230Vac | 50/60Hz



LED	3000K	Light Source	Luminaire
Power		54W	63,5W
Flux		9800lm	7040lm
Efficiency		181lm/W	111lm/W
LOR		-	72%
UGR		-	<25



Beam angle
Diffuse

Application



Weight
2,6Kg



Finishes

.25 Frost

Mandatory

43708 Surface fitting accessory (>2000mm)
43712 Pendant fitting accessory (>2000mm)

Optional

59062 Stainless steel fitting accessory (>2000mm)
59059 Wall fitting accessory

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class C
Model Identifier 28004772