



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.

Includes cable to connect modules with male and female plug connector.


Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.

IP44 | 48Vdc



 4000K	Light Source	Luminaire
Power	23W	23W
Flux	2800lm	2350lm
Efficiency	122lm/W	102lm/W
LOR	-	84%
UGR	-	-



Beam angle
Diffuse

Application



Weight
0,44Kg



Finishes

● .25 Frost

Included

Fitting accessories 0°
34x19x7mm



Mandatory

18105 Power cable (500mm)

2x0,35mm² (0,5m)

18106 Power cable (1000mm)

2x0,35mm² (1m)

18820 Power Supply 16W

On/Off

18821 Power Supply 30W

On/Off

18822 Power Supply 55W

On/Off

18823 Power Supply 75W

On/Off

18824 Power Supply 150W

On/Off

18833 LED Dimmer DALI

Optional

18107 Extension cable (1000mm)

2x0,35mm² (1m)

18108 Extension cable (5000mm)

2x0,35mm² (5m)

18831 Fitting accessories 45°

45x19,5x20mm