



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.

Includes cable to connect modules with male and female plug connector.


Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc



| LED        | 2200K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 9W           | 9W        |
| Flux       |       | 880lm        | 720lm     |
| Efficiency |       | 98lm/W       | 80lm/W    |
| LOR        |       | -            | 82%       |
| UGR        |       | -            | -         |



|             |            |
|-------------|------------|
| Beam angle  | Medium 30° |
| Application |            |
| Weight      | 0,18Kg     |



#### Finishes

● .25 Frost

#### Included

Fitting accessories 0°  
34x19x7mm



#### Mandatory

**18105** Power cable (500mm)

2x0,35mm<sup>2</sup> (0,5m)

**18106** Power cable (1000mm)

2x0,35mm<sup>2</sup> (1m)

**18820** Power Supply 16W

On/Off

**18821** Power Supply 30W

On/Off

**18822** Power Supply 55W

On/Off

**18823** Power Supply 75W

On/Off

**18824** Power Supply 150W

On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable (1000mm)

2x0,35mm<sup>2</sup> (1m)

**18108** Extension cable (5000mm)

2x0,35mm<sup>2</sup> (5m)

**18831** Fitting accessories 45°

45x19,5x20mm