



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.


Includes cable to connect modules with male and female plug connector.


Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.
IP44 | 48Vdc




 2500K	Light Source	Luminaire
Power	9W	9W
Flux	960lm	780lm
Efficiency	107lm/W	87lm/W
LOR	-	81%
UGR	-	-



Beam angle
Medium 30°

Application



Weight
0,18Kg



Finishes

● .25 Frost

Included

Fitting accessories 0°
34x19x7mm



Mandatory

18105 Power cable
2x0,35mm² (0,5m)
18106 Power cable
2x0,35mm² (1m)
18820 Power Supply 16W
On/Off
18821 Power Supply 30W
On/Off
18822 Power Supply 55W
On/Off
18823 Power Supply 75W
On/Off
18824 Power Supply 150W
On/Off
18833 LED Dimmer DALI

Optional

18107 Extension cable
2x0,35mm² (1m)
18108 Extension cable
2x0,35mm² (5m)
18831 Fitting accessories 45°
45x19,5x20mm