



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.


Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc




 <b>3000K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	<b>4,5W</b>	<b>4,5W</b>
<b>Flux</b>	<b>520lm</b>	<b>430lm</b>
<b>Efficiency</b>	<b>116lm/W</b>	<b>96lm/W</b>
<b>LOR</b>	-	<b>83%</b>
<b>UGR</b>	-	-



**Beam angle**  
**Medium 30°**

**Application**



**Weight**  
**0,09Kg**



#### Finishes

● .25 Frost

#### Included

Fitting accessories O°  
34x19x7mm



#### Mandatory

**18105** Power cable

2x0,35mm<sup>2</sup> (0,5m)

**18106** Power cable

2x0,35mm<sup>2</sup> (1m)

**18820** Power Supply 16W

On/Off

**18821** Power Supply 30W

On/Off

**18822** Power Supply 55W

On/Off

**18823** Power Supply 75W

On/Off

**18824** Power Supply 150W

On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable

2x0,35mm<sup>2</sup> (1m)

**18108** Extension cable

2x0,35mm<sup>2</sup> (5m)

**18831** Fitting accessories 45°

45x19,5x20mm