

4,5W / 460lm / 4000K / Medium 30° /  
310mm

62789



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.

Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc



LED	4000K	Light Source	Luminaire
Power		4,5W	4,5W
Flux		560lm	460lm
Efficiency		124lm/W	102lm/W
LOR		-	82%
UGR		-	-



Beam angle Medium 30°
Application 
Weight 0,09Kg



#### Finishes

● .25 Frost

#### Included

Fitting accessories O°  
34x19x7mm



#### Mandatory

**18105** Power cable (500mm)

2x0,35mm² (0,5m)

**18106** Power cable (1000mm)

2x0,35mm² (1m)

**18820** Power Supply 16W

On/Off

**18821** Power Supply 30W

On/Off

**18822** Power Supply 55W

On/Off

**18823** Power Supply 75W

On/Off

**18824** Power Supply 150W

On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable (1000mm)

2x0,35mm² (1m)

**18108** Extension cable (5000mm)

2x0,35mm² (5m)

**18831** Fitting accessories 45°

45x19,5x20mm