

6,8W / 550lm / 2200K / Medium 30° / 310mm

62819



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.

Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc



LED	2200K	Light Source	Luminaire
Power		6,8W	6,8W
Flux		670lm	550lm
Efficiency		99lm/W	81lm/W
LOR		-	82%
UGR		-	-



Beam angle  
Medium 30°

Application

Weight  
0,09Kg



#### Finishes

● .25 Frost

#### Included

Fitting accessories O°  
34x19x7mm



#### Mandatory

**18105** Power cable

2x0,35mm² (0,5m)

**18106** Power cable

2x0,35mm² (1m)

**18820** Power Supply 16W

On/Off

**18821** Power Supply 30W

On/Off

**18822** Power Supply 55W

On/Off

**18823** Power Supply 75W

On/Off

**18824** Power Supply 150W

On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable

2x0,35mm² (1m)

**18108** Extension cable

2x0,35mm² (5m)

**18831** Fitting accessories 45°

45x19,5x20mm