

6,8W / 700lm / 4000K / Medium 30° /  
310mm

62839



Design: O/M  
Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.  
Includes cable to connect modules with male and female plug connector.  
Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.  
Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc




LED	4000K	Light Source	Luminaire
Power		6,8W	6,8W
Flux		850lm	700lm
Efficiency		125lm/W	103lm/W
LOR		-	82%
UGR		-	-



Beam angle  
Medium 30°

Application

Weight  
0,09Kg



#### Finishes

● .25 Frost

#### Included

Fitting accessories 0°  
34x19x7mm



#### Mandatory

**18105** Power cable

2x0,35mm<sup>2</sup> (0,5m)

**18106** Power cable

2x0,35mm<sup>2</sup> (1m)

**18820** Power Supply 16W

On/Off

**18821** Power Supply 30W

On/Off

**18822** Power Supply 55W

On/Off

**18823** Power Supply 75W

On/Off

**18824** Power Supply 150W

On/Off

**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable

2x0,35mm<sup>2</sup> (1m)

**18108** Extension cable

2x0,35mm<sup>2</sup> (5m)

**18831** Fitting accessories 45°

45x19,5x20mm