



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.


Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc




|  |                     |                  |
|--|---------------------|------------------|
|  <b>4000K</b> | <b>Light Source</b> | <b>Luminaire</b> |
| <b>Power</b>   | 20,4W               | 20,4W            |
| <b>Flux</b>  | 2550lm              | 2100lm           |
| <b>Efficiency</b>  | 125lm/W             | 103lm/W          |
| <b>LOR</b>   | -                   | 82%              |
| <b>UGR</b>   | -                   | -                |



**Beam angle**  
Medium 30°

**Application**



**Weight**  
0,27Kg



#### Finishes

● .25 Frost

#### Included

Fitting accessories O°  
34x19x7mm



#### Mandatory

**18105** Power cable  
2x0,35mm² (0,5m)  
**18106** Power cable  
2x0,35mm² (1m)  
**18820** Power Supply 16W  
On/Off  
**18821** Power Supply 30W  
On/Off  
**18822** Power Supply 55W  
On/Off  
**18823** Power Supply 75W  
On/Off  
**18824** Power Supply 150W  
On/Off  
**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable  
2x0,35mm² (1m)  
**18108** Extension cable  
2x0,35mm² (5m)  
**18831** Fitting accessories 45°  
45x19,5x20mm