

34W / 3500lm / 4000K / Medium 30° /  
1455mm


62843



Design: O/M  
Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.  
Includes cable to connect modules with male and female plug connector.  
Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.  
Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.  
IP44 | 48Vdc



 <b>4000K</b>	<b>Light Source</b>	<b>Luminaire</b>
<b>Power</b>	34W	34W
<b>Flux</b>	4250lm	3500lm
<b>Efficiency</b>	125lm/W	103lm/W
<b>LOR</b>	-	82%
<b>UGR</b>	-	-



**Beam angle**  
Medium 30°

**Application**



**Weight**  
0,44Kg



#### Finishes

● .25 Frost

#### Included

Fitting accessories 0°  
34x19x7mm



#### Mandatory

**18105** Power cable  
2x0,35mm<sup>2</sup> (0,5m)  
**18106** Power cable  
2x0,35mm<sup>2</sup> (1m)  
**18820** Power Supply 16W  
On/Off  
**18821** Power Supply 30W  
On/Off  
**18822** Power Supply 55W  
On/Off  
**18823** Power Supply 75W  
On/Off  
**18824** Power Supply 150W  
On/Off  
**18833** LED Dimmer DALI

#### Optional

**18107** Extension cable  
2x0,35mm<sup>2</sup> (1m)  
**18108** Extension cable  
2x0,35mm<sup>2</sup> (5m)  
**18831** Fitting accessories 45°  
45x19,5x20mm