



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.


Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.
IP20 | 48Vdc




| | | |
|--|---------------------|------------------|
|  4000K | Light Source | Luminaire |
| Power | 18W | 18W |
| Flux | 2240lm | 1280lm |
| Efficiency | 124lm/W | 71lm/W |
| LOR | - | 57% |
| UGR | - | - |



Beam angle
Diffuse

Application



Weight
0,35Kg



Finishes

● .25 Frost

Included

Fitting accessories 0°
34x19x7mm



Mandatory

18105 Power cable

2x0,35mm² (0,5m)

18106 Power cable

2x0,35mm² (1m)

18820 Power Supply 16W

On/Off

18821 Power Supply 30W

On/Off

18822 Power Supply 55W

On/Off

18823 Power Supply 75W

On/Off

18824 Power Supply 150W

On/Off

18833 LED Dimmer DALI

Optional

18107 Extension cable

2x0,35mm² (1m)

18108 Extension cable

2x0,35mm² (5m)

18831 Fitting accessories 45°

45x19,5x20mm