



Design: O/M

Module with housing made of aluminium profile with integrated LED light source and frosted acrylic diffuser.

Includes cable to connect modules with male and female plug connector.

Components supplied separately: power supply, DALI dimmer, power cable, extension cable and fitting accessories 45°.

Maximum length of the sum of the modules: ≤4m.

LED CRI>80 / >50.000h, L80/B50 / 3-step MacAdam.
IP20 | 48Vdc



LED	3000K	Light Source	Luminaire
Power		6,8W	6,8W
Flux		790lm	440lm
Efficiency		116lm/W	65lm/W
LOR		-	56%
UGR		-	-



Beam angle
Diffuse

Application



Weight
0,09Kg



Finishes

☐ .25 Frost

Included

Fitting accessories 0°
34x19x7mm



Mandatory

18105 Power cable (500mm)
2x0,35mm² (0,5m)

18106 Power cable (1000mm)
2x0,35mm² (1m)

18820 Power Supply 16W
On/Off

18821 Power Supply 30W
On/Off

18822 Power Supply 55W
On/Off

18823 Power Supply 75W
On/Off

18824 Power Supply 150W
On/Off

18833 LED Dimmer DALI

Optional

18107 Extension cable (1000mm)
2x0,35mm² (1m)

18108 Extension cable (5000mm)
2x0,35mm² (5m)

18831 Fitting accessories 45°
45x19,5x20mm