

## U60 Made-to-measure

10W / 1140lm / 3000K / On/Off / Prismatic /  
839mm

63004

Design: O/M  
LED light source with good colour consistency and  
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



- Structure**  
1 Profile  
2 End caps  
3 Fitting accessories  
4 Profile coupling
- Diffuser**  
A Polycarbonate frost  
diffuser  
**Light Source**  
B LED Modules

LED	3000K	Light Source	Luminaire
Power		10W	12,2W
Flux		1835lm	1140lm
Efficiency		184lm/W	93lm/W
LOR		-	62%
UGR		-	<19



Beam angle  
Prismatic

Application



Weight  
0,51Kg



### Finishes

Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603211, 89603216