

## U60

### Made-to-measure

14W / 1600lm / 4000K / On/Off / Prismatic /  
1119mm

63038

Design: O/M

LED light source with good colour consistency and  
long operation lifespan.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP20 | 230Vac | 50/60Hz



#### Structure

- 1 Profile
- 2 End caps
- 3 Fitting accessories
- 4 Profile coupling

#### Diffuser

A Polycarbonate frost  
diffuser

#### Light Source

B LED Modules

LED	4000K	Light Source	Luminaire
Power		14W	17,1W
Flux		2600lm	1600lm
Efficiency		186lm/W	94lm/W
LOR		-	62%
UGR		-	<19



Beam angle  
Prismatic

#### Application



Weight  
0,57Kg



#### Finishes

Choose the length and layout of the system exactly as you want it, to  
model the right lighting functions for different tasks. For further  
information please contact: [support@om-light.com](mailto:support@om-light.com)

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603217

