

Tubo 70

24W / 3270lm / 4000K / DALI / Diffuse / 1752mm

63100



Design: Eduardo Souto de Moura
Surface or pendant luminaire with tubular shock-resistant frosted polycarbonate body with 70mm diameter.
Clear polycarbonate end caps with marked installation angles. Supplied with 30mm plastic cable gland that prevents condensation within luminaire.
Fitting accessories ordered separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP67 | IK08 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		24W	29,3W
Flux		4530lm	3270lm
Efficiency		189lm/W	112lm/W
LOR		-	72%
UGR		-	<25




Beam angle
Diffuse

Application



Weight
1,7Kg



Finishes

.25 Frost

Mandatory

43707 Surface fitting accessory

43711 Pendant fitting accessory

Optional

59058 Stainless steel fitting accessory

59059 Wall fitting accessory

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class B
Model Identifier 28004774