



Design: O/M

Surface luminaire with tubular shock-resistant clear polycarbonate diffuser and anti-condensation system comprising a valve that prevents condensation within the luminaire without affecting its high level of protection.

End caps in clear polycarbonate with marked installation angles.

Optic system with acrylic lens.

Equipped with 1m cable (H05RN-F) and a metallic cable gland.

Fitting accessories and IP68 connector supplied separately.

LED CRI>90 />50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP67 | IK08 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power		20W	24,4W
Flux		1800lm	1500lm
Efficiency		90lm/W	62lm/W
LOR		-	83%
UGR		-	<10



Beam angle
Super spot 10°

Application



Weight
0,5Kg



Finishes

.20 Clear


Mandatory

43707 Surface fitting accessory

Optional

43431 IP68 Connector
5 poles

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com





Set of 2 fitting accessories for surface version.

Finishes

● .20 Clear



Tubo Evo

IP68 Connector

43431



Tubo Evo IP68 Connector
5 poles, Ø7 to Ø12mm

Weight
0,04Kg

