

Tubo Evo

9.6W / 1300lm / 4000K / On/Off / Super
spot 10° / 535mm

63126



Design: O/M

Surface luminaire with tubular shock-resistant clear polycarbonate diffuser and anti-condensation system comprising a valve that prevents condensation within the luminaire without affecting its high level of protection.

End caps in clear polycarbonate with marked installation angles.

Optic system with acrylic lens.

Equipped with 1m cable (H05RN-F) and a metallic cable gland.

Fitting accessories and IP68 connector supplied separately.

LED CRI>80 />50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP67 | IK08| 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		9.6W	12W
Flux		1540lm	1300lm
Efficiency		160lm/W	108lm/W
LOR		-	84%
UGR		-	<10



Beam angle
Super spot 10°

Application



Weight
0,5Kg



Finishes

.20 Clear


Mandatory

43707 Surface fitting accessory

Optional

43430 IP68 Connector

4 poles





Set of 2 fitting accessories for surface version.

Finishes

● .20 Clear



Tubo Evo

IP68 Connector

43430



Tubo Evo IP68 Connector
4 poles, Ø7 to Ø12mm

Weight

0,004Kg

