



Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Adjustable version (orientable by 30° on the horizontal axis and 355° on the vertical axis).
Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



| LED | 2700K | Light Source | Luminaire |
|------------|---------|--------------|-----------|
| Power | 19W | 23,2W | |
| Flux | 2060lm | 1540lm | |
| Efficiency | 108lm/W | 66lm/W | |
| LOR | - | 75% | |
| UGR | - | <22 | |



Beam angle
Medium 28°



Application



Weight
0,5Kg



Ø95 (trim version)



Finishes

- .04 Matt White
- .05 Matt Black

Optional

- 59066** Flush accessory (12.5mm ceilings)
201x17mm
- 59067** Flush accessory (15mm ceilings)
201x19,5mm
- 59068** Flush accessory (25mm ceilings)
201x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F
Model Identifier BXR-27G2000-C-73