

# O/M

## Over Track

4,5W / 360lm / 4000K / On/Off / Spot 15° /  
ø85mm

63290



Design: O/M + Bartenbach GmbH

Track-mounted spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish. Spot-lens with individual complex surface ribs to provide a focal light and an extremely narrow beam. Orientable by 90° horizontal rotation and 330° vertical rotation. Driver included.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Driver included.  
IP20 | 230Vac | 50/60Hz



| LED 4000K           | Light Source | Luminaire |
|---------------------|--------------|-----------|
| Power               | 4,5W         | 5,8W      |
| Flux                | 620lm        | 360lm     |
| Efficiency          | 138lm/W      | 62lm/W    |
| LOR                 | -            | 58%       |
| Operating Condition | -            | 230Vac    |



Beam angle  
Spot 15°

Application

Weight  
0,64Kg



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E Model Identifier 2053560247L