

27W / 1840lm / 2700K / On/Off / Flood 52° /
1200mm

63340

Design: O/M + Bartenbach GmbH

Luminaire with housing of aluminium profile with electrostatic 100% polyester paint with textured-finish.

Focal-lens with complex surface and individual complex surface ribs to provide a focal point through an aperture for glare free area illumination.

Special springs available on request.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



| LED | 2700K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 27W | 32,9W |
| Flux | | 2400lm | 1840lm |
| Efficiency | | 89lm/W | 56lm/W |
| LOR | | - | 77% |
| UGR | | - | <13 |



Beam angle
Flood 52°

Application



Weight
0,6Kg



26x1194

Finishes

○ .01 White / RAL 9010

● .02 Black / RAL 9005

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class F Model Identifier 4053560342L

