

26W / 2480lm / 4000K / DALI / Medium 31° /
600mm

63439

Design: O/M + Bartenbach GmbH

Luminaire with housing of aluminium profile with
electrostatic 100% polyester paint with textured-
finish.

Focal-lens with complex surface and individual
complex surface ribs to provide a focal point through
an aperture for glare free area illumination.

Special springs available on request.

LED CRI>80 / >50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		26W	31,7W
Flux		3400lm	2480lm
Efficiency		131lm/W	78lm/W
LOR		-	73%
UGR		-	<10



Beam angle
Medium 31°

Application



Weight
0,5Kg



26x594

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of
material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class D
Model Identifier 4053560345H

