



Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
Lightcore optics for defined and perfectly controlled beam of light.
Recessing accessory supplied separately.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power		3,1W	4W
Flux		260lm	200lm
Efficiency		84lm/W	50lm/W
LOR		-	77%
UGR		-	<10



Beam angle
Medium 40°

Application



Weight



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

- 59042** Trimless accessory (12.5mm ceilings)
140x18mm
- 59043** Trimless accessory (15mm ceilings)
140x20mm
- 59044** Trimless accessory (25mm ceilings)
140x30mm

Optional

- 59083** Removal tool

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class G
Model Identifier 4053560312L

One Trimless

Trimless accessory (12.5mm
ceilings)

59042




Ø53



Trimless accessory One ø45
For 12.5mm ceilings.

Weight
0,01Kg



One Trimless

Trimless accessory (15mm
ceilings)

59043




Ø53



Trimless accessory One ø45
For 15mm ceilings.

Weight
0,01Kg



One Trimless

Trimless accessory (25mm
ceilings)

59044





Ø53



Trimless accessory One ø45
For 25mm ceilings.

Weight
0,01Kg





Removal tool

59083



Removal tool for Spot on
luminaires.

Finishes
.99