

Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.  
Lightcore optics for defined and perfectly controlled beam of light.  
Recessing accessory supplied separately.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power	3,1W		4W
Flux	260lm		230lm
Efficiency	84lm/W		58lm/W
LOR	-		88%
UGR	-		<16



Beam angle  
Flood 56°

Application



Weight



## Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

## Mandatory

- 59048 Trimless accessory (12.5mm ceilings)  
140x18mm
- 59049 Trimless accessory (15mm ceilings)  
140x20mm
- 59050 Trimless accessory (25mm ceilings)  
140x30mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com  
The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class G  
Model Identifier 4053560312L

## One Square Trimless

Trimless accessory (12.5mm  
ceilings)

59048




52x52



Trimless accessory One 45x45.  
For 12.5mm ceilings.

Weight  
0,01Kg

Finishes  
○ .01 White / RAL 9010



## One Square Trimless

Trimless accessory (15mm  
ceilings)

59049




52x52



Trimless accessory One 45x45.  
For 15mm ceilings.

Weight  
0,01Kg

Finishes  
○ .01 White / RAL 9010



## One Square Trimless

Trimless accessory (25mm  
ceilings)

59050



52x52



Trimless accessory One 45x45.  
For 25mm ceilings.

Weight  
0,01Kg

Finishes  
○ .01 White / RAL 9010

