

Design: O/M + Bartenbach GmbH


Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.


Lightcore optics for defined and perfectly controlled beam of light.

Recessing accessory supplied separately.


LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz




 3000K	Light Source	Luminaire
Power	3,1W	4W
Flux	260lm	200lm
Efficiency	84lm/W	50lm/W
LOR	-	77%
UGR	-	<10



Beam angle
Medium 40°

Application


Weight



Finishes

○ .01 White / RAL 9010

● .02 Black / RAL 9005

Mandatory

59048 Trimless accessory (12.5mm ceilings)
140x18mm

59049 Trimless accessory (15mm ceilings)
140x20mm

59050 Trimless accessory (25mm ceilings)
140x30mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations
2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class G
Model Identifier 4053560290L