

Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
Lightcore optics for defined and perfectly controlled beam of light.
Recessing accessory supplied separately.

LED CRI>90 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



| LED | 3000K | Light Source | Luminaire |
|------------|--------|--------------|-----------|
| Power | 3,1W | | 4W |
| Flux | 260lm | | 230lm |
| Efficiency | 84lm/W | | 58lm/W |
| LOR | - | | 88% |
| UGR | - | | <16 |



Beam angle
Flood 56°

Application



Weight



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

- 59048** Trimless accessory (12.5mm ceilings)
140x18mm
- 59049** Trimless accessory (15mm ceilings)
140x20mm
- 59050** Trimless accessory (25mm ceilings)
140x30mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class G
Model Identifier 4053560290L

One Square Trimless

Trimless accessory (12.5mm
ceilings)

59048




52x52



Trimless accessory One 45x45.
For 12.5mm ceilings.

Weight
0,01Kg

Finishes
○ .01 White / RAL 9010



One Square Trimless



52x52

Trimless accessory (15mm
ceilings)


59049



Trimless accessory One 45x45.
For 15mm ceilings.

Weight
0,01Kg

Finishes
○ .01 White / RAL 9010



One Square Trimless

Trimless accessory (25mm
ceilings)

59050



52x52



Trimless accessory One 45x45.
For 25mm ceilings.

Weight
0,01Kg

Finishes
○ .01 White / RAL 9010

