

3,1W / 240lm / 4000K / DALI / Flood 56° /
39x39mm

63561

Design: O/M + Bartenbach GmbH
Ceiling-recessed luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.
Lightcore optics for defined and perfectly controlled beam of light.
Recessing accessory supplied separately.

LED CRI>80 / >50.000h, L80/B10
2-step MacAdam / Power supply included.
IP20 | 230Vac | 50/60Hz



| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 3,1W | 4W |
| Flux | | 280lm | 240lm |
| Efficiency | | 90lm/W | 60lm/W |
| LOR | | - | 86% |
| UGR | | - | <16 |



Beam angle
Flood 56°

Application



Weight



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

- 59048 Trimless accessory (12.5mm ceilings)
140x18mm
- 59049 Trimless accessory (15mm ceilings)
140x20mm
- 59050 Trimless accessory (25mm ceilings)
140x30mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class G
Model Identifier 4053560313L