

4,5W / 470lm / 3000K / DALI / Flood 56° /  
ø85mm

63608



Design: O/M + Bartenbach GmbH

Surface/Pendant luminaire with aluminium die-cast body and heat sink with electrostatic 100% polyester paint finish.

Spot-lens with individual complex surface ribs to provide a focal light and an extremely narrow beam.

Fitting accessories ordered separately

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz

LED	3000K	Light Source	Luminaire
Power		4,5W	5,8W
Flux		520lm	470lm
Efficiency		116lm/W	81lm/W
LOR		-	90%
UGR		-	<16

Beam angle  
Flood 56°

Application

Weight  
0,53Kg

## Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

## Mandatory

59051 Accessory for pendant installation  
ø80x35mmFor the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

## Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class F  
Model Identifier 2053560257L