

4,5W / 360lm / 4000K / On/Off / Spot 15° /  
ø95mm

63746



Design: O/M + Bartenbach GmbH  
Ceiling-recessed luminaire with die-cast aluminium body and heat sink.  
Orientable by 30° on the horizontal axis and 355° on the vertical axis.  
Reflector built based on micro surfaces with complex geometry coated with aluminium alloy, creating a high-gloss, entirely mirrored surface. Accurate reflector for a defined and controlled beam of light, achieving the maximum efficiency.  
Reduced height <67mm.  
Recessing accessory for trimless version supplied separately.

LED CRI>80 / >50.000h, L80/B10  
2-step MacAdam / Power supply included.  
IP20 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		4,5W	5,8W
Flux		620lm	360lm
Efficiency		138lm/W	62lm/W
LOR		-	58%
UGR		-	<10



Beam angle  
Spot 15°

Application



Weight  
0,42Kg



Ø90 (trim version)



### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .21 Black+White

### Optional

59015 Accessory 12,5mm ceilings (flush installation)  
150x101x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations  
2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class E  
Model Identifier 2053560247L