

21W / 1410lm / 3000K / On/Off / Medium 31°
/ 911mm

63944



Design: O/M + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with electrostatic 100% polyester paint with textured-finish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision45 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories for pendant version ordered separately.

LED CRI>90 / >50.000h, L80/B10 / 2-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz



| LED | 3000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power | | 21W | 25,6W |
| Flux | | 1935lm | 1410lm |
| Efficiency | | 92lm/W | 55lm/W |
| LOR | | - | 73% |
| UGR | | - | <10 |



Beam angle
Medium 31°

Application



Weight
1,9Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Mandatory

54036 Pendant direct fitting accessory
54034 Clear Base
ø60x35mm