

14W / 1260lm / 4000K / DALI / Medium 31° /  
611mm

63976



Design: O/M + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with electrostatic 100% polyester paint with textured-finish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision45 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories for pendant version ordered separately.

LED CRI&gt;80 / &gt;50.000h, L80/B10 / 2-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



LED	4000K	Light Source	Luminaire
Power		14W	17,1W
Flux		1720lm	1260lm
Efficiency		123lm/W	74lm/W
LOR		-	73%
UGR		-	<10

Beam angle  
Medium 31°

Application

Weight  
1,3Kg

## Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

## Mandatory

54036 Pendant direct fitting accessory

56051 Clear Base DALI

ø60x35mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com