

39W / 3720lm / 4000K / DALI / Medium 31° /  
 911mm

**63981**


Design: O/M + Bartenbach GmbH

Surface or pendant luminaire with housing made of aluminium with electrostatic 100% polyester paint with textured finish.

Aluminium anodised end caps with electrostatic 100% polyester paint with textured-finish.

Housing and perforated cover plate made of aluminium with textured-paint finish. With the latest Bartenbach GmbH technology, inVision45 is a discreet solution, that can use great light distribution and visual comfort from a nearly invisible source. Fitting accessories for pendant version ordered separately.

 LED CRI>80 / >50.000h, L80/B10 / 2-step MacAdam  
 Power supply included.  
 IP20 | 230Vac | 50/60Hz


LED	4000K	Light Source	Luminaire
Power		39W	45,9W
Flux		5100lm	3720lm
Efficiency		131lm/W	81lm/W
LOR		-	73%
UGR		-	<10


 Beam angle  
**Medium 31°**

Application


 Weight  
**1,9Kg**

**Finishes**

- .01 White / RAL 9010
- .02 Black / RAL 9005

**Mandatory**
**54036** Pendant direct fitting accessory

**56051** Clear Base DALI

ø60x35mm

 For the specific supply of "DALI 2" drivers, please contact:  
[support@om-light.com](mailto:support@om-light.com)