

90W / 3400lm / 2700K / DALI / Diffuse  
indirect / 2821mm

64126



Design: Eduardo Souto de Moura

MGB Pendant Indirect module with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser with user friendly clipping system.

Steel end caps with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser for indirect light.

Three-phase track (On/Off or DALI) for installing spotlights.

Fitting accessories supplied separately.

LED CRI&gt;90 / &gt;50.000h, L80/B10 / 3-step MacAdam

Power supply included.


IP20 | 230Vac | 50/60Hz



LED	2700K	Light Source	Luminaire
Power		90W	130W
Flux		8500lm	3400lm
Efficiency		94lm/W	26lm/W
LOR		-	40%
UGR		-	<25

Beam angle  
Diffuse indirect

Application

Weight  
14Kg

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

56051 Clear base DALI

Ø60x35mm

54081 Aluminium base DALI

Ø60x37mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com