

90W / 3400lm / 2700K / DALI / Diffuse  
indirect / 2821mm

64126



Design: Eduardo Souto de Moura

MGB Pendant Indirect module with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser with user friendly clipping system.

Steel end caps with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser for indirect light.

Three-phase track (On/Off or DALI) for installing spotlights.

Fitting accessories supplied separately.

LED CRI&gt;90 / &gt;50.000h, L80/B10 / 3-step MacAdam

Power supply included.


IP20 | 230Vac | 50/60Hz



| LED        | 2700K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 90W          | 130W      |
| Flux       |       | 8500lm       | 3400lm    |
| Efficiency |       | 94lm/W       | 26lm/W    |
| LOR        |       | -            | 40%       |
| UGR        |       | -            | <25       |



Application

Weight  
14Kg

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

56051 Clear base DALI

Ø60x35mm

54081 Aluminium base DALI

Ø60x37mm

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com