

63W / 3300lm / 4000K / DALI / Diffuse
indirect / 1411mm

64141



Design: Eduardo Souto de Moura

MGB Pendant Indirect module with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser with user friendly clipping system.

Steel end caps with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser for indirect light.

Three-phase track (On/Off or DALI) for installing spotlights.

Fitting accessories supplied separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.


IP20 | 230Vac | 50/60Hz



| LED 4000K | Light Source | Luminaire |
|------------|--------------|-----------|
| Power | 63W | 90W |
| Flux | 8200lm | 3300lm |
| Efficiency | 130lm/W | 37lm/W |
| LOR | - | 40% |
| UGR | - | <25 |

Beam angle
Diffuse indirect

Application

Weight
7Kg

Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

56051 Clear base DALI

Ø60x35mm

54081 Aluminium base DALI

Ø60x37mm

For the specific supply of "DALI 2" drivers, please contact:
support@om-light.com