

23+45W / 850+1700lm / 2700K / On/Off /  
Diffuse Direct/ Indirect / 1411mm

64164



Design: Eduardo Souto de Moura

MGB Pendant Indirect module with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser with user friendly clipping system.

Steel end caps with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser for direct light and indirect light.

Fitting accessories supplied separately.

LED CRI>90 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



| LED        | 2700K | Light Source | Luminaire  |
|------------|-------|--------------|------------|
| Power      |       | 23+45W       | 33+65W     |
| Flux       |       | 2125+4250lm  | 850+1700lm |
| Efficiency |       | 94lm/W       | 26lm/W     |
| LOR        |       | -            | 40%        |
| UGR        |       | -            | <25        |



Beam angle  
Diffuse Direct/  
Indirect

Application



Weight  
7Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

**54034** Clear base  
Ø60x35mm  
**54080** Aluminium base  
Ø60x37mm