

23+45W / 1150+2300lm / 3000K / On/Off /  
Diffuse Direct/ Indirect / 1411mm

64172



Design: Eduardo Souto de Moura

MGB Pendant Indirect module with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser with user friendly clipping system.

Steel end caps with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser for direct light and indirect light.

Fitting accessories supplied separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz



| LED        | 3000K | Light Source | Luminaire   |
|------------|-------|--------------|-------------|
| Power      |       | 23+45W       | 33+65W      |
| Flux       |       | 2875+5750lm  | 1150+2300lm |
| Efficiency |       | 127lm/W      | 35lm/W      |
| LOR        |       | -            | 40%         |
| UGR        |       | -            | <25         |



Beam angle  
Diffuse Direct/  
Indirect

Application



Weight  
7Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

**54034** Clear base  
Ø60x35mm  
**54080** Aluminium base  
Ø60x37mm