

23+45W / 1150+2300lm / 4000K / On/Off /
Diffuse Direct/ Indirect / 1411mm

64180



Design: Eduardo Souto de Moura

MGB Pendant Indirect module with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser with user friendly clipping system.

Steel end caps with textured electrostatic 100% polyester paint.

Frosted acrylic diffuser for direct light and indirect light.

Fitting accessories supplied separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam

Power supply included.

IP20 | 230Vac | 50/60Hz




| LED | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-------------|
| Power | | 23+45W | 33+65W |
| Flux | | 2875+5750lm | 1150+2300lm |
| Efficiency | | 127lm/W | 35lm/W |
| LOR | | - | 40% |
| UGR | | - | <25 |



Beam angle
Diffuse Direct/
Indirect

Application

Weight
7Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

54034 Clear base
Ø60x35mm

54080 Aluminium base
Ø60x37mm