

63+126W / 3300+6600lm / 4000K / On/Off /
Diffuse Direct/ Indirect / 2821mm

64183



Design: Eduardo Souto de Moura
MGB Pendant Indirect module with housing made of aluminium profile with 25micron maximum corrosion resistance anodization with textured electrostatic 100% polyester paint.
Frosted acrylic diffuser with user friendly clipping system.
Steel end caps with textured electrostatic 100% polyester paint.
Frosted acrylic diffuser for direct light and indirect light.
Fitting accessories supplied separately.

LED CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP20 | 230Vac | 50/60Hz




| LED 4000K | Light Source | Luminaire |
|------------|--------------|-------------|
| Power | 63+126W | 90+180W |
| Flux | 8200+16400lm | 3300+6600lm |
| Efficiency | 130lm/W | 37lm/W |
| LOR | - | 40% |
| UGR | - | <25 |



Beam angle
Diffuse Direct/
Indirect



Weight
14Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

Mandatory

54034 Clear base
Ø60x35mm
54080 Aluminium base
Ø60x37mm