

5,6W / 370lm / 4000K / On/Off / Medium  
41° / ø45mm

64472



Design: O/M + Bartenbach GmbH  
Recessed spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish.  
Spot-lens with individual complex surface rips to provide a focal light and an extremely narrow beam.  
Orientable by 150° horizontal rotation and 330° vertical rotation.  
Driver included.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Driver included.  
IP20 | 230Vac | 50/60Hz



| LED                 | 4000K | Light Source | Luminaire |
|---------------------|-------|--------------|-----------|
| Power               |       | 5,6W         | 7W        |
| Flux                |       | 460lm        | 370lm     |
| Efficiency          |       | 82lm/W       | 53lm/W    |
| LOR                 |       | -            | 80%       |
| Operating Condition |       | -            | 230Vac    |



Beam angle  
Medium 41°

Application



Weight  
0,27Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

Optional

- 59072 1/4 CTO  
ø35x1,1mm
- 59073 1/2 CTO  
ø35x1,1mm
- 59074 Louvre  
ø35x2mm
- 59075 Soft diffuser  
ø35x2mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 |2019/2015/EU  
supplemented by 2021/340/EU Energy Consumption Labelling  
Ordinance. This product contains a light source of efficiency class G  
Model Identifier 4053560313L