

5,6W / 410lm / 2700K / On/Off / Flood 59° /  
ø45mm

64522

Design: O/M + Bartenbach GmbH

Track-mounted spotlight with die-cast aluminium body with electrostatic 100% polyester paint finish. Spot-lens with individual complex surface ribs to provide a focal light and an extremely narrow beam. Orientable by 150° horizontal rotation and 330° vertical rotation. Driver included.

LED CRI>90 / >50.000h, L80/B10  
2-step MacAdam / Driver included  
IP20 | 48Vdc



| LED                 | 2700K | Light Source | Luminaire |
|---------------------|-------|--------------|-----------|
| Power               |       | 5,6W         | 7W        |
| Flux                |       | 460lm        | 410lm     |
| Efficiency          |       | 82lm/W       | 59lm/W    |
| LOR                 |       | -            | 89%       |
| Operating Condition |       | -            | 48Vdc     |



Beam angle  
Flood 59°

Application

Weight  
0,27Kg



#### Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005

#### Optional

- 59072** 1/4 CTO  
ø35x1,1mm
- 59073** 1/2 CTO  
ø35x1,1mm
- 59074** Louvre  
ø35x2mm
- 59075** Soft diffuser  
ø35x2mm