

33W / 4085lm / 4000K / DALI / Diffuse /  
ø550mm

64580

Design: O/M

Ceiling-mounted luminaire made of aluminium body with electrostatic 100% polyester paint with textured-finish suitable for adverse climate conditions.

Frosted acrylic diffuser with perfect light uniformity.

LED: CRI>80 / >50.000h, L80/B10 / 3-step MacAdam  
Power supply included.  
IP43 | 230Vac | 50/60Hz



| LED        | 4000K | Light Source | Luminaire |
|------------|-------|--------------|-----------|
| Power      |       | 33W          | 38,8W     |
| Flux       |       | 5840lm       | 4085lm    |
| Efficiency |       | 177lm/W      | 105lm/W   |
| LOR        |       | -            | 70%       |
| UGR        |       | -            | <25       |



Beam angle  
Diffuse

Application

Weight  
6,1Kg



Finishes

- .01 White / RAL 9010
- .02 Black / RAL 9005
- .03 Grey / RAL 9006

For the specific supply of "DALI 2" drivers, please contact:  
support@om-light.com

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains light sources of efficiency class C  
Model Identifier 89603017