

Sky Pendant

33W / 4085lm / 4000K / On/Off / Diffuse /
ø550mm

64589

Design: O/M

Pendant luminaire made of aluminium body with electrostatic 100% polyester paint with textured-finish suitable for adverse climate conditions.

Frosted acrylic diffuser with perfect light uniformity.


Suspension system with millimetric height adjustment ordered separately.


Power supply base made of clear polycarbonate, clear power cable (3x0,75mm²) and steel suspension cables (1,2mm) with millimetric height adjustment system supplied separately.

Accessories supplied separately.

LED: CRI>80 / >50.000h, L80/B10 / 3-step MacAdam
Power supply included.
IP43 | 230Vac | 50/60Hz




 LED	4000K	Light Source	Luminaire
Power	33W	38,8W	
Flux	5840lm	4085lm	
Efficiency	177lm/W	105lm/W	
LOR	-	70%	
UGR	-	<25	



Beam angle
Diffuse

Application

Weight
6,1Kg



Finishes

- ☐ .01 White / RAL 9010
☒ .02 Black / RAL 9005
☐ .03 Grey / RAL 9006

Mandatory

59080 Pendant fitting accessory
54034 Clear Base
ø60x35mm

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains light sources of efficiency class C
Model Identifier 89603017