




Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP44 | 100mA



 3000K	Light Source	Luminaire
Power	3,7W	3,7W
Flux	395lm	315lm
Efficiency	107lm/W	85lm/W
LOR	-	80%
UGR	-	<16




Beam angle
Flood 42°

Application



Weight
0.08Kg



Finishes

○ .04 Matt White

● .05 Matt Black

Mandatory

59088 Driver On/Off [100mA]
138x30x21mm


59089 Driver DALI [100mA]
144x30x21mm

59090 Driver PhaseCut [100mA]
122x41x23mm

59091 Driver 1-10V [120mA]
130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com
The 5-year guarantee applies only when the luminaire and driver are supplied together.


Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRH-30G1000-B-83



Go

Driver DALI [1 luminaire]


59088



Driver On/Off for Go ø50 [100mA]
230Vac | 50/60Hz | Class II


Weight
0,1Kg

Finishes
.99




Go

Driver DALI [1 luminaire] 59089




Driver DALI for Go ø50 [100mA]
230Vac | 50/60Hz | Class II

Weight	Finishes
0,06Kg	.99




Go

Driver PhaseCut [1 luminaire] 59090




Driver PhaseCut for Go ø50
[100mA]
230Vac | 50/60Hz | Class II

Weight	Finishes
0,08Kg	.99



Go

Driver 1-10V [1 luminaire] 59091



Driver 1-10V for Go ø50 [120mA]
230Vac | 50/60Hz | Class II

Weight	Finishes
0,07Kg	.99