




Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP44 | 100mA



 3500K	Light Source	Luminaire
Power	3,7W	3,7W
Flux	410lm	330lm
Efficiency	111lm/W	89lm/W
LOR	-	80%
UGR	-	<22




Beam angle
Flood 60°

Application



Weight
0.08Kg



- Finishes
- .04 Matt White
 - .05 Matt Black

- Mandatory
- 59088 Driver On/Off [100mA]
138x30x21mm
 - 59089 Driver DALI [100mA]
144x30x21mm
 - 59090 Driver PhaseCut [100mA]
122x41x23mm
 - 59091 Driver 1-10V [120mA]
130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com
The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations
2019/2020/EU supplemented by 2021/341 |2019/2015/EU
supplemented by 2021/340/EU Energy Consumption Labelling
Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRH-35G1000-B-83