




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP44 | 400mA / 200mA



 LED	2700K	Light Source	Luminaire
Power	14W / 7W	14W / 7W	14W / 7W
Flux	2270lm / 1135lm	1815lm / 910lm	1815lm / 910lm
Efficiency	162lm/W	130lm/W	130lm/W
LOR	-	80%	80%
UGR	-	<13	<13



Beam angle  
Flood 42°

Application



Weight  
0.37Kg



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory

- 59117** Driver On/Off [400mA]  
147x43x30mm
- 59116** Driver On/Off [200mA]  
147x43x30mm
- 59119** Driver DALI [400mA]  
144x30x21mm
- 59118** Driver DALI [200mA]  
144x30x21mm
- 59121** Driver PhaseCut [400mA]  
111x22x52mm
- 59120** Driver PhaseCut [180mA]  
102x49x29mm
- 59123** Driver 1-10V [400mA]  
163x30x21mm
- 59122** Driver 1-10V [200mA]  
130x30x20mm

#### Optional

- 59154** Louvre  
ø45x4mm
- 59155** Elliptical diffuser  
ø45x4mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXRE-27G20FB-C-83