




Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP44 | 400mA / 200mA



	2700K	Light Source	Luminaire
	Power	14W / 7W	14W / 7W
	Flux	2270lm / 1135lm	1815lm / 910lm
	Efficiency	162lm/W	130lm/W
	LOR	-	80%
	UGR	-	<19



Beam angle  
Flood 60°

Application



Weight  
0.37Kg



Ø90



#### Finishes

- .04 Matt White
- .05 Matt Black

#### Mandatory


- 59117** Driver On/Off [400mA]  
147x43x30mm
- 59116** Driver On/Off [200mA]  
147x43x30mm
- 59119** Driver DALI [400mA]  
144x30x21mm
- 59118** Driver DALI [200mA]  
144x30x21mm
- 59121** Driver PhaseCut [400mA]  
111x22x52mm
- 59120** Driver PhaseCut [180mA]  
102x49x29mm
- 59123** Driver 1-10V [400mA]  
163x30x21mm
- 59122** Driver 1-10V [200mA]  
130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

#### Data according to regulations


2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E  
Model Identifier BXRE-27G20FB-C-83



Go

Driver On/Off [1 luminaire]


59117



Driver On/Off for Go ø100  
[400mA]  
230Vac | 50/60Hz | Class II

Weight  
0,08Kg


Finishes  
.99



Go

Driver On/Off [1 luminaire]



59116



Driver On/Off for Go ø100  
[200mA]  
230Vac | 50/60Hz | Class II


Weight  
0,08Kg

Finishes  
.99




Go

Driver DALI [1 luminaire] 59119




Driver DALI for Go ø100 [400mA]  
230Vac | 50/60Hz | Class II

Weight	Finishes
0,08Kg	.99



Go




Driver DALI [1 luminaire] 59118



Driver DALI for Go ø100 [200mA]  
230Vac | 50/60Hz | Class II


Weight  
0,08Kg

Finishes  
.99



Driver PhaseCut for Go ø100  
[400mA]  
230Vac | 50/60Hz | Class II

Weight  
**0,11Kg**



## Go

Driver PhaseCut [1 luminaire]


59120



Driver PhaseCut for Go ø100  
[180mA]  
230Vac | 50/60Hz | Class II

Weight  
0,13Kg






Driver 350mA for Dot  
1 to 6 luminaires  
IP65 | 230Vac | 50/60Hz | Class II

Weight  
**0,06Kg**





Driver 1-10V for Go ø100 [200mA]  
230Vac | 50/60Hz | Class II

Weight  
0,07Kg

