




Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP44 | 300mA / 150mA




| | | |
|--|--------------|----------------|
|  4000K | Light Source | Luminaire |
| | Power | 10W / 5W |
| | Flux | 1555lm / 780lm |
| | Efficiency | 156lm/W |
| | LOR | 79% |
| | UGR | <10 |
| | | |



Beam angle
Spot 20°

Application



Weight
0.37Kg



Ø90



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory


- 59109** Driver On/Off [300mA]
147x43x30mm
- 59108** Driver On/Off [150mA]
147x43x30mm
- 59111** Driver DALI [300mA]
144x30x21mm
- 59110** Driver DALI [150mA]
144x30x21mm
- 59113** Driver PhaseCut [300mA]
102x51x30mm
- 59112** Driver PhaseCut [150mA]
102x49x29mm
- 59115** Driver 1-10V [300mA]
130x30x20mm
- 59114** Driver 1-10V [150mA]
130x30x20mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.


Data according to regulations

2019/2020/EU supplemented by 2021/341 [2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class E
Model Identifier BXRE-40G10FB-C-83




Go

Driver On/Off [1 luminaire] 59109



Driver On/Off for Go ø100
[300mA]
230Vac | 50/60Hz | Class II


| | |
|--------|----------|
| Weight | Finishes |
| 0,08Kg | .99 |



Go

Driver On/Off [1 luminaire]


59108



Driver On/Off for Go ø100
[150mA]
230Vac | 50/60Hz | Class II


Weight
0,08Kg

Finishes
.99




Go

Driver DALI [1 luminaire] 59111




Driver DALI for Go ø100 [300mA]
230Vac | 50/60Hz | Class II

| | |
|--------|----------|
| Weight | Finishes |
| 0,08Kg | .99 |




Go

Driver DALI [1 luminaire] 59110




Driver DALI for Go ø100 [150mA]
230Vac | 50/60Hz | Class II

| | |
|--------|----------|
| Weight | Finishes |
| 0,08Kg | .99 |




Driver PhaseCut [1 luminaire] 59113




Driver PhaseCut for Go ø100
[300mA]
230Vac | 50/60Hz | Class II

| | |
|--------|----------|
| Weight | Finishes |
| 0,09Kg | .99 |



Go


Driver PhaseCut [1 luminaire] 59112



Driver PhaseCut for Go ø100
[150mA]
230Vac | 50/60Hz | Class II

Weight
0,13Kg


Finishes
.99



Go

Driver 1-10V [1 luminaire]


59115



Driver 1-10V for Go ø100 [300mA]
230Vac | 50/60Hz | Class II


Weight
0,07Kg

Finishes
.99



Go

Driver 1-10V [1 luminaire] 59114



Driver 1-10V for Go ø100 [150mA]
230Vac | 50/60Hz | Class II

| | |
|--------|----------|
| Weight | Finishes |
| 0,07Kg | .99 |