



6,7W / 3,7W / 585lm / 330lm / 4000K / Spot  
20° / ø75mm

64781

Design: O/M  
Ceiling-recessed luminaire made of aluminium die-cast.  
Recessing system with spring clips.  
Recessing accessory for flush version supplied separately.

LED CRI>90 / >50.000h, L80/B10  
3-step MacAdam / Power supply not included  
IP44 | 180mA / 100mA



 4000K	Light Source	Luminaire
Power	6,7W / 3,7W	6,7W / 3,7W
Flux	720lm / 400lm	585lm / 330lm
Efficiency	107lm/W	87lm/W
LOR	-	81%
UGR	-	<16



Beam angle  
Spot 20°

Application



Weight  
0.21Kg



Ø65



#### Finishes

○ .04 Matt White

● .05 Matt Black

#### Mandatory

**59093** Driver On/Off [180mA]

147x43x30mm

**59092** Driver On/Off [100mA]

92x28x21mm

**59095** Driver DALI [180mA]

144x30x21mm

**59094** Driver DALI [100mA]

144x30x21mm

**59097** Driver Phase-Cut [180mA]

102x49x29mm

**59096** Driver Phase-Cut [100mA]

122x41x23mm

**59099** Driver 1-10V [180mA]

130x30x20mm

**59098** Driver 1-10V [120mA]

130x30x20mm

#### Optional

**59069** Flush accessory (12.5mm ceilings)

176x17mm

**59070** Flush accessory (15mm ceilings)

176x19,5mm

**59071** Flush accessory (25mm ceilings)

176x29,5mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: [support@om-light.com](mailto:support@om-light.com)

The 5-year guarantee applies only when the luminaire and driver are supplied together.

#### Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F  
Model Identifier BXRH-40G1000-B-83