

3,7W / 300lm / 2700K / Flood 42° /
50x50mm


64797



Design: O/M
Ceiling-recessed luminaire made of aluminium die-cast.
Recessing system with spring clips.

LED CRI>90 / >50.000h, L80/B10
3-step MacAdam / Power supply not included
IP44 | 100mA



 2700K	Light Source	Luminaire
Power	3,7W	3,7W
Flux	375lm	300lm
Efficiency	101lm/W	81lm/W
LOR	-	80%
UGR	-	<16



Beam angle
Flood 42°

Application



Weight
0.08Kg



45x45



Finishes

- .04 Matt White
- .05 Matt Black

Mandatory

- 59088** Driver On/Off [100mA]
138x30x21mm
- 59089** Driver DALI [100mA]
144x30x21mm
- 59090** Driver PhaseCut [100mA]
122x41x23mm
- 59091** Driver 1-10V [120mA]
130x30x20mm

Optional

- 59140** Flush accessory (12.5mm ceilings)
110X56X16,5mm
- 59141** Flush accessory (15mm ceilings)
110X56X19,5mm
- 59148** Louvre
ø25x4mm
- 59149** Elliptical diffuser
ø25x4mm

The cutout dimensions are for plasterboard ceilings. For other type of material please contact: support@om-light.com

The 5-year guarantee applies only when the luminaire and driver are supplied together.

Data according to regulations

2019/2020/EU supplemented by 2021/341 | 2019/2015/EU supplemented by 2021/340/EU Energy Consumption Labelling Ordinance. This product contains a light source of efficiency class F
Model Identifier BXRH-27G1000-B-83